



TRAFITAL

S.p.A.

acciai trafilati - pelati - rettificati

1953 - 2013



www.trafital.it - info@trafital.it - Capitale sociale € 5.500.000 - R.E.A. VA n.163765 - Reg. Impr. VA 01216480127 - C.F.- P.IVA 01216480127
 Sede e Stabilimento: Via A. Colombo, 301 - 21055 GORLA MINORE (VA) - Tel. +39. 0331.368.900 - Fax +39.0331.368.940
 Filiali con Magazzino: Via del Tappezziere, 7 - 40138 BOLOGNA - Tel. +39. 051. 53.10.93 - Fax +39.051.53.23.27
 Strada per Settimo 388/9 - 10156 TORINO - Tel. +39.011.27.33.707 - Fax +39.011.27.33.677

Tabella	Tolleranza di rettilineità - <i>Straightness tolerances</i>
Normativa UNI	EN 10278:2002

PROFILI PIATTI FLATS BARS

Materiale		Larghezza < 120 mm	Larghezza ≥ 120 mm L/S < 10	Larghezza ≥ 120 mm L/S ≥ 10 (Larghi Piatti)
S235JR / S355 / 11SMnPb (C<0,25%)	Toll. Larghezza	1,5 mm/mt	2 mm/mt	2 mm/mt
	Toll. Spessore	1,5 mm/mt	2 mm/mt	2,5 mm/mt
C45 / 39NiCrMo3	Toll. Larghezza	1,5 mm/mt	2 mm/mt	2,5 mm/mt
	Toll. Spessore	2 mm/mt	2,5 mm/mt	3 mm/mt

PROFILI TONDI ROUNDS BARS

Materiale	Tutte le dimensioni
S235JR / S355 / 11SMnPb (C<0,25%)	1 mm/mt
C45 / 39NiCrMo3	1,5 mm/mt

PROFILI QUADRI ED ESAGONI SQUARES AND HEXAGONS BARS

Materiale	D ≤ 75 mm	D > 75 mm
S235JR / S355 / 11SMnPb (C<0,25%)	1 mm/mt	1,5 mm/mt
C40 / 39NiCrMo3	2 mm/mt	2,5 mm/mt

Siamo gli specialisti in :

- Trafilati di grandi dimensioni
- Piatti Spessore fino 100 mm larghezza fino 500 mm
- Quadri fino a 160 mm
- Rettificati fino a 160 mm
- Angolari trafilati a lati uguali e disuguali fino 100x100x10
- Alberi scanalati
- Profili speciali su disegno del Cliente
- Misure per chiavette h9 x h11

We are specialized in:

- Large Cold Drawn
- Flats Thickness up to 100 mm Width up to 500 mm
- Squares up to 160 mm
- Ground steel up to 160 mm
- Cold-drawn steel angles up to 100x100x10
- Splined Shaft
- Special Profile to according to drawing
- Flats and squares for Keysteel h9 x h11